ITW SHAKEPROOF INDUSTRIAL PRODUCTS

FINISH CODE REVISION LEVEL

BRIEF DESCRIPTION:

ME-0 EZINC-BAKE-CHROMATE-SEALER-RoHS

ME

0

REV DATE: 10/10/2017

GENERAL DESCRIPTION

.0003 MIN ELECTRO-ZINC CLEAR TRIVALENT CHROMATE WITH SEALER. !!!MUST BE RoHS COMPLIANT!!!

APPEARANCE

GLOSSY UNIFORM COLOR SILVER-WHITE IN A SEALER

ADHESION AND DUCTILITY

TO BE TESTED IN ACCORDANCE TO ASTM B571 (SCOTCH TAPE TEST)

<u>CORROSION REQUIREMENTS</u> RED RUST: <u>168</u> WHITE CORRIOSION: <u>96</u>

SALT SPRAY TESTS TO BE PERFORMED PER ASTM B117

COATING THICKNESS REQUIREMENTS

MIN THICKNESS: .0003 MAX THICKNESS: .0005 THICKNESS SHALL BE TESTED PER ASTM E376

STRESS RELIEF

PARTS TO BE BAKED AT 400 DEGREES F FOR 8 HOURS WITHIN 1 HOUR OF BASE PLATING

QUALITY CONTROL

VISUALLY INSPECT FOR UNIFORMITY OF COLOR AND SURFACE APPEARANCE, FREEDOM FROM TEARS, BARE SPOTS, POWDERY FILM, SLOUGHING OFF OF FILM, AND BLISTERING

PROCESS TO

PRINT DATE:

10/10/2017