

ITW SHAKEPROOF INDUSTRIAL PRODUCTS

FINISH
CODE

REVISION
LEVEL

BRIEF DESCRIPTION:

UR-0 GEOMET 321-SILVER-ROHS

UR

0

REV DATE: 6/23/2009

GENERAL DESCRIPTION

GEOMET 321 IS COMPOSED OF ZINC AND ALUMINIUM FLAKES IN AN INORGANIC BINDER WITH " VL" LUBE TOPCOAT. !!!MUST BE RoHS COMPLIANT!!!

APPEARANCE

SILVER

ADHESION AND DUCTILITY

TO BE TESTED IN ACCORDANCE TO ASTM B571 (SCOTCH TAPE TEST)

CORROSION REQUIREMENTS

RED RUST: 1000

WHITE CORRIOSION: 200

SALT SPRAY TESTS TO BE PERFORMED PER ASTM B117

COATING THICKNESS REQUIREMENTS

8-10 UM

STRESS RELIEF

NOT REQUIRED

QUALITY CONTROL

VISUALLY INSPECT FOR UNIFORMITY OF COLOR AND SURFACE APPEARANCE, FREEDOM FROM TEARS, BARE SPOTS, POWDERY FILM, SLOUGHING OFF OF FILM, AND BLISTERING

PROCESS TO

PRINT DATE:

6/8/2016