

# ITW SHAKEPROOF INDUSTRIAL PRODUCTS

FINISH  
CODE

REVISION  
LEVEL

## BRIEF DESCRIPTION:

UV-0 GEOMET 720 PLUS-GEOLBLACK ROHS

**UV**

**1**

REV DATE: 6/27/2016

## GENERAL DESCRIPTION

GEOMET 720 PLUS COMPOSED OF ZINC AND ALUMINUM FLAKES IN AN INORGANIC BINDER FOLLOWED BY PLUS TOPCOAT TO MEET FRICTIONAL REQUIREMENTS. !!!MUST BE RoHS COMPLIANT!!!

## APPEARANCE

BLACK

## ADHESION AND DUCTILITY

TO BE TESTED IN ACCORDANCE TO ASTM B571 (SCOTCH TAPE TEST)  
COEFFICIENT OF FRICTION: 0.15-0.21( $\mu$ ) TESTED IN ACCORDANCE WITH ISO 16047

## CORROSION REQUIREMENTS

RED RUST: 1500

WHITE CORRIOSION:

SALT SPRAY TESTS TO BE PERFORMED PER ASTM B117

## COATING THICKNESS REQUIREMENTS

MIN THICKNESS: .0002

MAX THICKNESS: .0009

TESTED PER ASTM B487

## STRESS RELIEF

NOT REQUIRED

## QUALITY CONTROL

VISUALLY INSPECT FOR UNIFORMITY OF COLOR AND SURFACE APPEARANCE, FREEDOM FROM TEARS, BARE SPOTS, POWDERY FILM, SLOUGHING OFF OF FILM, AND BLISTERING

## PROCESS TO

GE F69A2E2

PRINT DATE:

6/27/2016