

ITW SHAKEPROOF INDUSTRIAL PRODUCTS

FINISH
CODE

REVISION
LEVEL

BRIEF DESCRIPTION:

UY-0 GEOMET P PER JDM F13H-RoHS

UY

0

REV DATE: 1/17/2017

GENERAL DESCRIPTION

ZINC AND ALUMINUM FLAKES IN AN INORGANIC (DACROSEAL) BINDER FOLLOWED BY TOPCOAT TO MEET FRICTIONAL REQUIREMENT. !!!MUST BE RoHS COMPLIANT!!!

APPEARANCE

GRAY

ADHESION AND DUCTILITY

TO BE TESTED PER JDM F13H

CORROSION REQUIREMENTS

RED RUST: 240

WHITE CORRIOSION:

SALT SPRAY TESTS TO BE PERFORMED PER ISO 9227

COATING THICKNESS REQUIREMENTS

PER JDM F13H

STRESS RELIEF

NOT REQUIRED

QUALITY CONTROL

VISUALLY INSPECT FOR UNIFORMITY OF COLOR AND SURFACE APPEARANCE, FREEDOM FROM TEARS, BARE SPOTS, POWDERY FILM, SLOUGHING OFF OF FILM, AND BLISTERING

PROCESS TO

JDM F13H

PRINT DATE:

3/2/2017