

# ITW SHAKEPROOF INDUSTRIAL PRODUCTS

FINISH  
CODE

REVISION  
LEVEL

**BRIEF DESCRIPTION:**

VR-0 DELTA KL100-BLK-WHITE HD

**VR**

**0**

REV DATE: 3/6/2012

**GENERAL DESCRIPTION**

DELTA-PROTEKT KL 100 BASECOAT 2 COATS FOLLOWED BY DELTS-SEAL GZ BLACK TOPCOAT. PAINT HEAD WHITE PER GE COLOR CHIP #12H2427. USE POLY-URETHANE PAINT TO PREVENT CHIPPING.

**APPEARANCE**

HEAD OF SCREW TO BE UNIFORM WHITE

**ADHESION AND DUCTILITY**

TO BE TESTED IN ACCORDANCE TO ASTM B571 (SCOTCH TAPE TEST)

**CORROSION REQUIREMENTS**

RED RUST: 1000

WHITE CORRIOSION:

SALT SPRAY TESTS TO BE PERFORMED PER ASTM B117

**COATING THICKNESS REQUIREMENTS**

PER DELTA-PROTEKT PROCESS

**STRESS RELIEF**

NOT REQUIRED

**QUALITY CONTROL**

VISUALLY INSPECT FOR UNIFORMITY OF COLOR AND SURFACE APPEARANCE, FREEDOM FROM TEARS, BARE SPOTS, POWDERY FILM, SLOUGHING OFF OF FILM, AND BLISTERING

**PROCESS TO**

PRINT DATE:

6/8/2016